

Weld-X™

For Spot Welding & Welding Repairs



The high arc temperatures generated by the Weld-X™ easily fuse all standard thermocouple materials, including platinum and tungsten. Wires can be welded in pairs in gages of #20 or finer, and individually for gages as heavy as #16.

Welded surface connections to ferrous materials are generally the strongest and most easily made. However, very satisfactory direct attachments can be made to aluminum, titanium, copper, and zinc based alloys.

WICHITECH
INDUSTRIES INC.
"CLEARLY SUPERIOR"™

<u>CHARACTERISTIC</u>	<u>SPECIFICATION</u>
Size3 1/4" High, 6" Wide, 6 1/4" Deep
Weight6 1/4 pounds
Stored Weld Energy5 to 50 Watt seconds
Wire Gauge	All standard wire types between 16 and 30 gauge
Cycle TimeCan perform 5 to 10 welds per minute, depending on the energy setting
ControlsProvides energy adjustment control and visual and aural indication of weld charge and cycle completion
PowerWill operate from either AC line voltage or self-charging internal battery. Will perform several hundred welds on charged battery. 120V AC 60 Hz standard. 220 VAC 50 Hz available upon request.

For more information, to place an order, or for a personal demonstration, please contact:

WichTech Industries, Inc.
1120 N. Charles Street • Suite 103
Baltimore, Maryland 21201
United States of America

www.wichitech.com
(800) 776-4277
410/244-1966
FAX 410/244-1968

P/N
F4SPT000

Visa and MasterCard accepted.